



19mm A/F

MTN/1120I Series

General purpose industrial accelerometer

Applications

- Paper machinery
- General industry
- Pumps, fans, etc.
- Air handling units
- Machine tools

Technical Specification

Standard Sensitivity	100 mV/g ±10% nominal at 80 Hz
Frequency Response	2 Hz to 10 kHz ±5% (-3 dB at 0.8 Hz)
Mounted Base Resonance	20 kHz (nominal)
Isolation	Base isolated
Dynamic Range	±80g
Transverse Sensitivity	Less than 5%
Electrical Noise	0.1 mg max
Current Range	0.5 mA to 8 mA
Temperature Range	-55 to 140 ºC
Temperature Sensitivity	0.08 %/ºC
Bias Voltage	12 Volts (nominal)
DC Supply	+18 to 30 Volts
Case Material	Stainless steel
Mounting Torque	8 Nm
Weight	45 gms (nominal)
Sealing	IP67
Mating Connector	MTN/MH008
Options	Connector, side entry, mating cable assemblies, various mounts, other

sensitivities (see table).

ORDER CODE PART №	MOUNTING	xx =OPTIONAL SENSITIVITY RANGE AVAILABLE (+/- 10%)
MTN/1120IF-xx MTN/1120IQ-xx MTN/1120IF6-xx MTN/1120IF1/4- xx	10-32 UNF FEMALE QUICK FIT FEMALE M6 FEMALE 1⁄4" UNF FEMALE	0-10 mV/g 0-30 mV/g 0-50 mV/g
FOR OTHER MOUNTINGS SEE OVER PAGE		0-500 mV/g

MONITRAN LTD MONITOR HOUSE HAZLEMERE RD PENN BUCKS UK HP10 8AD Tel: +44 (D) 1494 816569 Fax: +44 (D) 1494 812256 email: infd@monitran.co.uk www.monitran.co.uk Monitran reserves the right to alter the specification without prior notice

Mounting Adapters and Studs

Studs and Grub Screws

Quick Fit Adapters

Product

Code MS010

MS055

MS072

MS102

MS117





Male Studs		
Product	From	То
Code	FIOIII	10
MS036	1/4" - 28 UNF	M6
MS039	1/4" - 28 UNF	10 - 32 UNF
MS067	1/4" - 28 UNF	M8
MS068	1/4" - 28 UNF	1/4" - 28 UNF
MS124	1/4" - 28 UNF	M10
MS132	1/4" - 28 UNF	M12

1120 Studs		
Product Code	From	То
MS021	1/4" - 28 UNF	M8

Other Adapters



Mounting Adapters			
Product Code	From	То	
MS011	1/4" - 28 UNF Male	Q/F Female	
MS013	1/4" - 28 UNF Male	Glue base	
MS033	1/4" - 28 UNF Male	Q/F Female	
MS061	1/4" - 28 UNF Male	10 - 32 UNF Male	
MS079	1/4" - 28 UNF Male	Q/F Female	

Isolation		
Product Code	From	То
MS034 MS027	1/4" - 28 UNF Male M6 Male	1/4" - 28 UNF Female M6 Female

1120 Quick Fit (Q/F)

То

Glue base

M8 Male

M6 Male

10 - 32 UNF Male

1/4" - 28 UNF Male

From

1120 Q/F Male

1120 Q/F Male 1120 Q/F Male 1120 Q/F Male

1120 Q/F Female

1120 Q/F Male

System Connection

